

# Control pedestal for offshore

## U23 / 23



The control pedestal U23 / 23 accommodate the devices necessary for control and monitoring. Ready wired, it can be quickly and easily installed on the sea deck. The housing (pedestal head) is made of seawater-resistant aluminium.

Surface treatment:  
 Priming and structure-finishing paint  
 Standard colour RAL 7032 pebble-grey



### Technical data:

Operation temperature	-40°C to +85°C
Degree of protection	IP66

Example

**U23 / 23 / N61.../N62... / H / PW / 2D / PQ / KLV / X**

### Housing

U23/23	With 1 narrow cover with pillar-gasket
U23/23A	With 1 narrow cover without drilling in the housing
IA	Monitoring devices cover with gasket for max. 2 monitors 72 x 72 mm or 4 monitors 72 x 36 mm and max. 6 indicating devices pos. 28, 29
RS	Pillar 108mm Ø 670 mm height with flange quadratic or round

### Masterswitch / Control-switch

N61	HG Masterswitch with ball handle and indicating labels
N62	KN Control-switch with knob and indicating label

**-HG -01 Z P -A05 P134 -X**

### Axis 1: direction 3-4

(Standard contacts gold-plated 2A 250 V AC15)

01	2 contacts	Standard contact - arrangement see page 140
02	4 contacts	z.B.
03	6 contacts	A05 MS21
04	8 contacts	A0500 MS21-00

*A99 contact - arrangement according customer request*

Z	Spring return		
R	Friction brake		
P	Potentiometer		
	P131	T396 2 x 0,5 kOhm	I max. 1 mA
	P132	T396 2 x 1 kOhm	I max. 1 mA
	P133	T396 2 x 2kOhm	I max. 1 mA
	P134	T396 2 x 5 kOhm	I max. 1 mA
	P135	T396 2 x 10 kOhm	I max. 1 mA

*More potentiometers on request!*

U23 / 23 / N61.../N62... / H / PW / 2D / PQ / KLV / X

Command and indicating devices		
H	Heating	20 Watt 220 or 110V 50/60 Hz
PV	Mushroom head push button latching	22 latching with indicating label 1 Ö
P	Mushroom head push button	22 with indicating label 1 S
D	Push button	22 with indicating label 1 S
W	Selector switch 0-1	22 with indicating label 1 S
L	Indicator light	22 with indicating label Diode 24 Volt
L	Indicator light	22 with indicating label Diode 230 Volt AC
	Contact block additional	1 S or 1 Ö
L	Indicator light	22 with indicating label Diode 24 Volt protection IP65
L	Indicator light	10 with indicating label Diode 24 Volt protection IP65
Display devices		
PQ	Powermeter PQ 72 1 mA DC	Engraved your instructions
PQI	Powermeter PQ 72 1 mA DC illuminated 24 Volt	Engraved your instructions
PQ	Powermeter PQ 72 x 36 1 mA DC	Engraved your instructions
PQI	Powermeter PQ 72 x 36 1 mA DC illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 100/200/1A illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 x 36 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 x 36 100/200/1A illuminated 24 Volt	Engraved your instructions
Wiring		
KLV on terminal block 2,5 mm <sup>2</sup> with wire line 0,75 mm <sup>2</sup>		
Special model		
X	Special / customer specified	

3

